



VALVE REGULATED LEAD ACID BATTERIES WARRANTY POLICY

PSG BATTERY LINE

TWO YEAR GUARANTEE

Power Battery guarantees to the original end user that VRLA batteries with Advanced Gel technology will be free of defects in Material and workmanship for 24 months from date of shipment from Power Battery Company. Power Battery Co. must be notified immediately upon suspicion of any possible defects and be given the authority to inspect any questionable sites. If Power Battery Company determines the batteries to be defective due to faulty material or workmanship, it will repair or replace them at its option, without charge, FOB factory.

GENERAL OPERATING & WARRANTY CONDITIONS

1. Charging voltage 2.25-2.35 VPC at 25 deg.C. The batteries are assumed to be used in cycling service. If used with solar panels as chargers, there must be a high quality charge controller between the solar panels and batteries.
2. Temperature:
 - A. Average annual ambient temperature shall not exceed 77 deg. F/25 deg. C.
 - B. Cell temperature shall not exceed 92 deg. F/33 deg. C. for more than 30 days per year.
3. The vent caps must not be tampered with or removed.
4. The batteries must not be contaminated by any foreign matter.
5. This warranty does not apply to broken containers, covers or battery terminals which have been frozen or damaged due to neglect or abuse such as fire, flooding, explosives or any acts of nature.
6. Registration, installation and periodic inspection reports regarding temperature and conditions of use are to be maintained by the end user and made available to Power Battery on request to support any warranty adjustment claim.
7. All batteries should be recharged immediately following a discharge.
8. Batteries shall be boost charged every 3-6 months, while in storage, prior to final installation.
9. No battery will be covered under warranty in the event of improper installation and maintenance such as overcharging, undercharging, charging or installing in reverse polarity.
10. All maintenance functions (handling, storage and installation) must be performed in accordance with Power's VRLA Field Service Manual

Note: Power batteries are rated to supply at least 95% of capacity at C/8 upon shipment. These batteries will reach 100% capacity after approximately 25 cycles.

The user is responsible for the shipping costs of all warranty replacements.

Power Battery Company, Inc.
Corporate Headquarters
25 McLean Blvd,
Paterson, NJ 07514
www.powerbattery.com

Power Battery Company, Inc.
Canadian Headquarters
770 Thomas Ave.
Iberville, Quebec, Canada, J2X 5E7
www.powerbattery.com

Power Battery Company, Inc.
European Headquarters
Premier Way, Abbey Park
Romsey, Hampshire SO519AQ UK
www.powbat.co.uk